



### Cartridge, graphite grease

Grease cartridge, **molybdenum disulphide and graphite**, particularly suitable for heavy-duty lubrication.

For hand-held and compressed-air grease nipples.

**Features:** excellent adhesiveness Water repellent Wear-proof and anti-corrosion



Code	€	Content (g)	ø (mm)	Length (mm)
P502650010	---	600	56	300



### Grease cartridge for high temperatures

Grease cartridge, **lithium-based complex**, particularly resistant to high temperatures.

For hand-held and compressed-air grease nipples.

**Features:** for lubricating bearings.

**Operating temperature -15÷160°C**



Code	€	Content (g)	ø (mm)	Length (mm)
P502650015	---	600	56	300



### Greasing kit

Greasing kit including: lever grease gun with 30 cm. hose, 4-jaw fitting for ball-head grease nipples, 600 g universal lithium-based grease cartridge.




Code	€
P502700005	---



### High-pressure grease syringe

High-pressure grease syringe in burnished steel for grease with taper Lub nozzle, for flared-head grease nipples.




Code	€	Carrying capacity (g)	B (mm)	C (mm)	L (mm)
P503050050	---	50	30	120	160
P503050150	---	150	40	180	245



### Push grease syringe, re-entering type

Push grease syringe, re-entering type, for grease with Zerch nozzle, for ball-head grease nipples.



Code	€	Carrying capacity (g)	B (mm)	C (mm)	L (mm)
P503100050	---	50	30	130	180
P503100200	---	200	45	160	220




### High-pressure grease gun

High-pressure grease gun, hand loading.

Operable with one single hand, easily reaching high pressures.

Consisting in: stiff coupling and head.



Code	€	Content (cm³)	Max. pressure (bar)	Supply (cm³)	Coupling	B (mm)	C (mm)
P503150120	---	120	400	0,5	1/8 gas	40	150

LUBRICATION