



Hand-held lever transfer pump

Diesel-oil transfer pump for drums, piston-operated, self-priming, with 1 m PVC retention pipe with galvanized steel spout and 810 mm rigid pipe.



Code	€	For barrels (Kg)	Flow rate per pumping (ml)
P504320005	---	200	370



Hand-held rotary transfer pump

Diesel-oil rotary transfer pump for drums, reversible, blowing and suction reversed by changing the direction of rotation of the handle, self-priming, with a 1 m PVC pipe, 1 m steel immersed hose complete with filter, flow rate of 70 l/min, G 2" ring nut.



Code	€	For barrels (Kg)
P504261010	---	200



Oil syringe

Oil suction and pressure syringe in brass.



Code	€	Content (g)	Dimensions (mm)
P504304022	---	250	40x220
P504305028	---	500	50x280



Code	€	Content (g)	Dimensions (mm)
P504305050	---	1000	50x500




Oil level peep hole in aluminium

Oil level peep hole in aluminium, glass window, white star-shaped indicator, oil seal in fibre, fastening hexagon for wrench.



Code	€	Thread	A (mm)	B (mm)	Hexagon CH (mm)
P502170005	---	G 3/8	8	8	22
P502170010	---	G 1/2	8	9	27



Code	€	Thread	A (mm)	B (mm)	Hexagon CH (mm)
P502170015	---	G 3/4	10	10	32



Flexible spray end pipe

Flexible spray end pipe for emulsified oil and water.



Code	€	Length (mm)	Thread (G)
P506600300	---	300	1/4-3/8
P506600400	---	400	1/4-3/8
P506600500	---	500	1/4-3/8



Code	€	Length (mm)	Thread (G)
P506600600	---	600	1/4-3/8
P506600700	---	700	1/4-3/8

LUBRICATION