



### Pillar-type drill, with tiltable board, with clamp



Pillar-type drill, completed with tiltable board with clamp, suitable for series machining and maintenance visit, with tiltable and height-adjustable piece holder board with integrated clamp.

**Technical features:** - supply: 380 Volt three-phase - power: 2.5 kW - maximum drilling diameter: 32 mm - number of spins: 230÷1.910 min-1 - column diameter: 102 mm - distance board/spindle: 670 mm - spindle/base distance: 1,270 mm - working distance column/spindle: 230 mm - dimensions of work desktop: 400x400 mm.



Code	€	Morse taper	Sleeve stroke (mm)	Chuck speed no.	Overall dimensions (mm)	Weight (Kg)
R505900005	---	4	140	9	600x380x1800	260



### Impulse screwdriver



Impulse screwdriver, **high tightening torque** with high impact power suitable for vehicle wheel bolting, bolting operations on building sites and in dockyards, high speed to increase the speed of execution.

**Universal socket wrench holder with 1/2" male drive fitting** to hold a wide variety of tools, right and left rotation, mechanical impact mass with low recoil, additional handle with rubber coating for easier handling and a reduction in rebound for the operator.



Code	€	Power (W)	Power supply (V)	Revolutions no. (1/min)	Square bush holder (Inches)	Screw max ø (M)	Max tightening torque (Nm)	Reversibility	Weight (Kg)
R250450005	---	710	230	2200	1/2	20	440	yes	3,2



### Impulse screwdriver



Impulse screwdriver, **high tightening torque** with high impact power suitable for lorry wheel bolting, bolting of mechanical and steel structures, as well as for construction of boilers and piping systems.

**Universal socket wrench holder with 3/4" male drive fitting** to hold a wide variety of tools, right and left rotation, mechanical impact mass with low recoil, additional handle with two-position support for easier handling, suspension bracket for the balancer.

**Equipment** - 1 supplementary grip - 1 suspension bracket.



Code	€	Power (W)	Power supply (V)	Revolutions no. (1/min)	Square bush holder (Inches)	Screw max ø (M)	Max tightening torque (Nm)	Reversibility	Weight (Kg)
R250350005	---	800	230	950	3/4	24	600	yes	5,7



### Impulse screwdriver



Impulse screwdriver, **high tightening torque** with high impact power suitable for heavy-duty bolting on building machines, in the construction of industrial vehicles, in heavy industry and petrochemical industry.

**Universal socket wrench holder with 1" male drive fitting** to hold a wide variety of tools, right and left rotation, mechanical impact mass with low recoil, additional handle with two-position support for easier handling, suspension bracket for the balancer.

**Equipment** - 1 supplementary grip - 1 suspension bracket.



Code	€	Power (W)	Power supply (V)	Revolutions no. (1/min)	Square bush holder (Inches)	Screw max ø (M)	Max tightening torque (Nm)	Reversibility	Weight (Kg)
R250400005	---	920	230	860	1	30	1000	yes	7,3

BENCHTOP AND COLUMN DRILLS  
SCREWDRIVERS AND TAPPING DRILLS