



## Tap screw

Tap screw with integrated reversing gear and rapid recoil.  
Electronically variable speeds with differentiated number of spins between tapping and recoil phases to optimise operating time, enbloc motor casing with aluminium inerts, ergonomic rear grip for maximum operator comfort, supplied without tap chuck, to choose between fixed and oscillating type.



R201410010

R201410015



Code	€	Power (W)	Power supply (V)	No. of turns in thread (1/min)	No. of revolutions in return (1/min)	Thread max (M)	Spindle shaft	Weight (Kg)	Accessory
R201410005	◆	450	230	0÷450	0÷680	10	B 12	1,6	-
R201410010	◆	-	-	-	-	-	-	-	fixed spindle
R201410015	◆	-	-	-	-	-	-	-	oscillating spindle



## Angle grinder for 115mm grindstone



Angle grinder for **115 mm diameter grinders**, lowered gear head to work in narrow places, direct cooling for high overload capability and long working life, **protection against the accidental restarting**, safety switch for controlled switching-on of the tool and high safety for the operator, rotation-resistant protective guard to guarantee maximum safety even in case of grinding wheel breakage.

**Equipment:** - 1 additional Vibration Control handgrip - 1 rotation protection cap - 1 wrench - 1 fixing nut - 1 fixing ring - 1 plastic suitcase.



Code	€	Power (W)	Power supply (V)	Wheel ø (mm)	Revolutions no. (1/min)	Vibrations (m/s <sup>2</sup> )	Weight (Kg)
R202250005	◆	720	230	115	11000	6,5	1,9



## Angle grinder for 115mm grindstone

Angle grinder for **115 mm diameter grinders**, lowered gear head to work in narrow places, stator coil completely covered with epoxy resin for long working life, safety switch for controlled switching-on of the tool and high safety for the operator, shaft locking button at the side to avoid accidental insertion when working in restricted spaces, rotation-resistant protective guard to guarantee maximum safety even in case of grinding wheel breakage.

**Equipment:** - 1 additional handgrip - 1 rotation protection cap - 1 wrench - 1 fixing nut - 1 fixing ring.



Code	€	Power (W)	Power supply (V)	Wheel ø (mm)	Revolutions no. (1/min)	Vibrations (m/s <sup>2</sup> )	Weight (Kg)
R203050005	◆	800	230	115	11800	9,4	1,8



## Angle grinder for 125 mm grindstone



Angle grinder for **125 mm diameter grinders**, gear head can be turned in 90° steps, speed regulation, direct cooling for high overload capability and long working life, supplementary Vibration Control handle.

**Protection against the accidental restarting**, safety switch for controlled switching-on of the tool and high safety for the operator, rotation-resistant protective guard to guarantee maximum safety even in case of grinding wheel breakage. **E**

**Equipment:** - 1 additional handgrip - 1 rotation protection cap - 1 wrench - 1 fixing nut - 1 fixing ring.



Code	€	Power (W)	Power supply (V)	Wheel ø (mm)	Revolutions no. (1/min)	Vibrations (m/s <sup>2</sup> )	Weight (Kg)
R204000005	◆	900	230	125	2800÷11000	7,5	1,9