



eSafe female safety connection - 320 series hose connection

eSafe female safety connection in compliance with the standard ISO 4414 and EN 983, in galvanized steel / brass.

Operating temperature -20 +100 °C.



| Code | € | Pipe connection ø (mm) | Nominal ø (mm) | Air flow rate (l/min) | Max operating pressure (bar) | Min burst pressure (bar) | Connection force (N) |
|------------|---|------------------------|----------------|-----------------------|------------------------------|--------------------------|----------------------|
| R802250005 | ◆ | 6,3 | 7,6 | 2250 | 16 | 140 | 86 |
| R802250010 | ◆ | 8 | 7,6 | 2250 | 16 | 140 | 86 |
| R802250015 | ◆ | 10 | 7,6 | 2250 | 16 | 140 | 86 |
| R802250020 | ◆ | 13 | 7,6 | 2250 | 16 | 140 | 86 |



Female eSafe safety connection - Series 320 threaded male

eSafe female safety connection pursuant to the standard standards ISO 4414 and EN 983, in galvanized steel/brass.

Operating temperature -20 +100 °C.



| Code | € | Male thread (BSPT) | Nominal ø (mm) | Air flow rate (l/min) | Max operating pressure (bar) | Min burst pressure (bar) | Connection force (N) |
|------------|---|--------------------|----------------|-----------------------|------------------------------|--------------------------|----------------------|
| R802100005 | ◆ | 1/4" | 7,6 | 2250 | 16 | 140 | 86 |
| R802100010 | ◆ | 3/8" | 7,6 | 2250 | 16 | 140 | 86 |
| R802100015 | ◆ | 1/2" | 7,6 | 2250 | 16 | 140 | 86 |



eSafe female safety connection - Male threaded series 315

eSafe female safety connection in compliance with the standard ISO 4414 and EN 983, in galvanized steel / brass.

Operating temperature -20 +100 °C.



| Code | € | Male thread (BSPT) | Nominal ø (mm) | Air flow rate (l/min) | Max operating pressure (bar) | Min burst pressure (bar) | Connection force (N) |
|------------|---|--------------------|----------------|-----------------------|------------------------------|--------------------------|----------------------|
| R803400005 | ◆ | 1/4" | 7,5 | 1950 | 16 | 140 | 86 |
| R803400010 | ◆ | 3/8" | 7,5 | 1950 | 16 | 140 | 86 |
| R803400015 | ◆ | 1/2" | 7,5 | 1950 | 16 | 140 | 86 |



Female eSafe safety connection - Series 320 threaded female

eSafe female safety connection pursuant to the standard standards ISO 4414 and EN 983, in galvanized steel-zinc-plated brass .

Operating temperature -20 ÷ 100 °C



| Code | € | Female thread (BSP) | Nominal ø (mm) | Air flow rate (l/min) | Max operating pressure (bar) | Min burst pressure (bar) | Connection force (N) |
|------------|---|---------------------|----------------|-----------------------|------------------------------|--------------------------|----------------------|
| R802150005 | ◆ | 1/4" | 7,6 | 2250 | 16 | 140 | 86 |
| R802150010 | ◆ | 3/8" | 7,6 | 2250 | 16 | 140 | 86 |
| R802150015 | ◆ | 1/2" | 7,6 | 2250 | 16 | 140 | 86 |



eSafe female safety connection - Female threaded series 315

eSafe female safety connection in compliance with the standard ISO 4414 and EN 983, in galvanized steel / brass.

Operating temperature -20 +100 °C.



| Code | € | Female thread (BSP) | Nominal ø (mm) | Air flow rate (l/min) | Max operating pressure (bar) | Min burst pressure (bar) | Connection force (N) |
|------------|---|---------------------|----------------|-----------------------|------------------------------|--------------------------|----------------------|
| R803450005 | ◆ | 1/4" | 7,5 | 1950 | 16 | 140 | 86 |
| R803450010 | ◆ | 3/8" | 7,5 | 1950 | 16 | 140 | 86 |
| R803450015 | ◆ | 1/2" | 7,5 | 1950 | 16 | 140 | 86 |

CONNECTORS AND FITTINGS FOR PNEUMATIC TOOLS