



Male connection without valve - Series 320 Stream-line connection

Male connection without valve, in tempered galvanised steel.



Code	€	Pipe ø (mm)	Nominal ø (mm)	Air flow rate (l/min)	Max operating pressure (bar)	Min burst pressure (bar)
R801700005	---	6,5x10	7,6	2250	16	140
R801700010	---	8x12	7,6	2250	16	140
R801700015	---	11x16	7,6	2250	16	140



Rotating adaptor Stream-line connection - Threaded male

Adaptor Stream-line connection for pipe Item R81005, in brass.

- Working temperature -20 ÷ 80°C
- Maximum working pressure 12bar
- Flow 2,100 l/min.



Code	€	Pipe ø (mm)	Male thread (BSPT)
R802850005	---	6,5x10	1/4"
R802850010	---	8x12	3/8"
R802850015	---	9,5x13,5	1/4"

Code	€	Pipe ø (mm)	Male thread (BSPT)
R802850020	---	9,5x13,5	3/8"
R802850025	---	11x16	1/2"



Fixed adaptor Stream-line connection - Threaded male

Adaptor Stream-line connection for Item R81005, in brass.

- Working temperature -20 ÷ 80°C
- Maximum working pressure 12bar
- Flow 2,100 l/min.




Code	€	Pipe ø (mm)	Male thread (BSPT)
R802900005	---	6,5x10	1/4"
R802900010	---	8x12	1/4"

Code	€	Pipe ø (mm)	Male thread (BSPT)
R802900020	---	9,5x13,5	1/4"
R802900025	---	9,5x13,5	3/8"



Male threaded barbed-hose push-on connector

Male threaded barbed-hose push-on connector in nickel-plated brass.



Code	€	Pz.	A (BSP)	A1 (mm)	B (mm)	C (mm)	L (mm)	Hexagon (mm)
R804050005	---	10	1/8"	6	18	6,5	30	12
R804050015	---	10	1/8"	8	18	6,5	30	12
R804050105	---	10	1/4"	6	18	7,5	31	14
R804050115	---	10	1/4"	8	19,5	8,5	33,5	14
R804050125	---	10	1/4"	10	19,5	8,5	33,5	14
R804050130	---	10	1/4"	12	19,5	8,5	33,5	14

Code	€	Pz.	A (BSP)	A1 (mm)	B (mm)	C (mm)	L (mm)	Hexagon (mm)
R804050215	---	10	3/8"	10	21	9	35	17
R804050220	---	10	3/8"	12	21	9	35	17
R804050310	---	10	1/2"	12	22	11	42	22
R804050315	---	10	1/2"	14	22	11	42	22
R804050320	---	10	1/2"	16	22	11	42	22



Universal male threaded dry-break coupler

Universal male threaded dry-break ball coupler, black shock-absorbent cap in nylon, nickel-plated brass body, universal use with all kinds of couplings.



Code	€	Pz.	Male thread (BSP)	Profile
R805050005	---	20	1/4"	Italy
R805050010	---	20	3/8"	Italy

Code	€	Pz.	Male thread (BSP)	Profile
R805050015	---	20	1/2"	Italy