



Multipurpose harness

Multi-purpose harness (**mod. HT 45**) with standard buckles, a dorsal anchor and a sternal D-shaped forged steel, 5 adjustment points, leg loops and a very comfortable seat belt.
Compliant with standard **EN 361**.



Code	€	Size	Weight (Kg)
S551050005	— ◊	M	0,99
S551050010	— ◊	XL	0,99



Positioning lanyard

Adjustable positioning rope Titan FPL, in polyamide \varnothing 12 mm, complete with snap hook in light alloy twist-Lock, **complying with standard EN 358**.



Code	€	Length (m)	Carabiner type	No. of spring catches
S550140005	— ◊	2	Twist-Lock	1
S550140010	— ◊	2	Twist-Lock	2



Retention string

Safety lanyard (**Titan F12 model**), in polyamide \varnothing 12 mm, without connectors, terminal eyelets with protective plastic element.
Compliant with standard **EN 354**.



Code	€	Length (m)
S551350005	— ◊	1,5



Guided fall limiter

Guided type fall arrester (**Titan model**) in stainless steel with a 12 mm \varnothing polyamide rope and ring nut, possibility of operating with hands free, particularly suitable for operating on **pitched roofs** or where retractable devices cannot be used, lanyard for attaching to the 0.30 m harness with quick connector.
Compliant with standard **EN 353-2**.



Code	€	Length (m)
S550680005	— ◊	15



Retention string

Adjustable safety lanyard (mod. LC), in polyamide, \varnothing 12 mm, without shock absorber, complete with two snap hooks, **complying with standard EN 354**.



Code	€	Length (m)
S600200005	— ◊	2