



Shock-absorbing lanyard

Anti-crash rope mod. LCA with energy absorber, in polyamide \varnothing 12 mm, with two screwgate carabiners, **complying with standard EN 355.**



Code	€	Length (m)
S600350005	—	1,5



Shock-absorbing lanyard

Anti-crash rope mod. LCAD with energy absorber, in polyamide \varnothing 12 mm, with two screwgate carabiners and two scaffolding connectors, **complying with standard EN 355.**



Code	€	Length (m)
S600400010	—	2



Lanyard with energy absorber

Lanyard with energy absorber (mod. Kernmantel), tested on edges, with 2 locking carabiners. Compliant with standard **EN 355.**



Code	€	Length (m)
S551440005	—	1,5



String with two-ended energy absorber

Lanyard with double-ended energy absorber (Titan A3 model), 30 mm polyester tape, breaking strength greater than 15 KN, with ring-type snap hook and two 63 mm scaffold hooks. Compliant with standard **EN 355.**



Code	€	Length (m)
S551450005	—	2



Lanyard with energy absorber

Lanyard with energy absorber (mod. Kernmantel), tested on edges, with a Twist-Lock steel carabiner and a 55 mm wide opening hook. Compliant with standard **EN 355.**



Code	€	Length (m)
S551580005	—	1



Fall protection kit for roof-workers

Fall protection kit for roofs (Titan model) composed of: harness with 2 anchor points with dorsal and sternal attachment (through slots) and automatic guided device with anchor line with rope and with connection to the harness of 30 cm. Compliant with standards **EN 361** and **EN 353-2.**



Code	€	Rope length (m)
S551600005	—	10