



Retractable fall protection device

Retractable fall arrest device (Aviabloc model) with integrated energy absorber, protective casing and 2 locking carabiners, polyamide fabric tape, maximum length 2.5 m, ideal for work in limited height, reduced fall distance thanks to to the rapid activation stop mechanism. Compliant with standard **EN 360**.



 Code
 €
 Length (m)

 S552500005
 -,--- ◊
 2,5



Retractable fall protection device

Retractable anti-fall device (**Turbolite model**) with compact and ultra-resistant carter with revolving element, 2 m anti-abrasion belt, weight 0.8 Kg, with 2 locking carabiners. It requires less free fall space under the user's feet (the maximum weight must not exceed 140 kg) with anchoring above the head (fall factor 0); with anchorage between the connector D and above the line of the feet (fall factor 2) the weight of the operator must not exceed 100 Kg. Compliant with standard **EN 360**.




Code	€	Length (m)	
S551750005	🛇	2.5	



Retractable fall protection device with self-retracting lifeline

Retractable anti-fall device with automatic recall **(Falcon model)** with galvanized steel cable ø 4.8 mm, nylon casing with high resistance against impacts, fall indicator, fast action locking mechanism with quick stop in few centimeters, it does not require annual recrification by the manufacturer and the revision can be made by the user with the instructions attached to the device, tested and approved also for horizontal applications if used with the appropriate optional accessories. Compliant with the standard **EN 360**.



Tracter Retractable fall limiter with self-retracting lifeline

Retractable anti-fall device with automatic recall **(Alko PK model)** with energy absorber, galvanized steel cable, plastic protection, supplied with locking carabiner and revolving carabiner with fall indicator.

Approved for horizontal use.

Compliant with standard EN 360

Code	€	Rope length (m)
S551330005	-, 🛇	6
S551330010	-, 🛇	10
S551330015	-, 🛇	20



MILLER