






format) Vice for drills

Drill vice with special cast iron body, hardened steel jaws, one smooth and the other with longitudinal and transversal prisms, both with a sunken flat area.



Code	€	Jaws width (mm)	Tightening opening (mm)	Centre distance between basins (mm)	Weight (Kg)
C558070080	-, ♦	80	70	110	4
C558070100	-, ♦	100	110	140	9





format Couple of jaws

Pair of jaws in alloy steel, with transversal and longitudinal prismatic seats, flat area lowered, provided with 4 screws.

Replacement bit for drills code C55807.



Code	€	Jaws width (mm)	
C558110080	-, ♦	80	
C558110100	-, ♦	100	



Code	€	Jaws width (mm)	
C558110125	-, ♦	125	
C558110160	-, ♦	160	



Drill clamp, special cast body, tempered reversible jaws, ground and burnished, one smooth jaw, the other with longitudinal and transverse prisms, both jaws have a support surface for clamping flat pieces, with the possibility of universal

Application: for clamping parts on drills.



Code	€	Jaws width (mm)	Tightening opening (mm)	Centre distance between basins (mm)	Weight (kg)
C553720110	-, ♦	110	130	140	9,5
C553720135	-, ♦	135	160	170	13,5



Code	€	Jaws width (mm)	Tightening opening (mm)	Centre distance between basins (mm)	Weight (kg)
C553720160	-, 💠	160	220	210	25



Three-dimensional piece lock

Three-dimensional piece lock in anodized aluminium for assembly on milling machines and drills.

Available either with T plug for slot.



Code	€	Clamping type	A (mm)	B (mm)
C556300005	-,	Simple	220	140

