



← Previous page

Code	€	Pz.	M	D (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602250105	---	10	20	21,7	35x35	28	14	22
C602250110	---	1	16	23,7	40x40	32	16	24
C602250115	---	1	20	23,7	40x40	32	16	24
C602250120	---	1	22	23,7	40x40	32	16	24
C602250125	---	1	16	27,7	44x44	36	18	28
C602250130	---	1	20	27,7	44x44	36	18	28

Code	€	Pz.	M	D (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602250135	---	1	22	27,7	44x44	36	18	28
C602250140	---	1	24	27,7	44x44	36	18	28
C602250145	---	1	24	29,7	48x48	38	19	30
C602250150	---	1	27	31,6	50x50	40	20	32
C602250155	---	1	30	35,6	54x54	44	22	36
C602250160	---	1	36	41,6	65x65	52	26	42



### Plug for T slot without hole

Plug for T slot without hole No. 508R, in hardening and tempering steels.



Code	€	D (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602270005	---	7,7	13x13	10	6	8
C602270010	---	9,7	15x15	12	6	10
C602270015	---	11,7	18x18	14	7	12
C602270020	---	13,7	22x22	16	8	14
C602270025	---	15,7	25x25	18	9	16
C602270030	---	17,7	28x28	20	10	18
C602270035	---	19,7	32x32	24	12	20

Code	€	D (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602270040	---	21,7	35x35	28	14	22
C602270045	---	23,7	40x40	32	16	24
C602270050	---	27,7	44x44	36	18	28
C602270055	---	31,6	50x50	40	20	32
C602270060	---	35,6	54x54	44	22	36
C602270065	---	41,6	65x65	52	26	42



### Plug for T slot double length

Plug for T slot double length No 508L, in hardening and tempering steels.



Code	€	Pz.	M	D (mm)	L (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602280005	---	10	6	7,7	26	13	10	6	8
C602280010	---	10	8	9,7	30	15	12	6	10
C602280015	---	10	10	11,7	36	18	14	7	12
C602280020	---	10	12	13,7	44	22	16	8	14
C602280025	---	10	14	15,7	50	25	18	9	16
C602280030	---	10	16	17,7	56	28	20	10	18

Code	€	Pz.	M	D (mm)	L (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602280035	---	1	18	19,7	64	32	24	12	20
C602280040	---	1	20	21,7	70	35	28	14	22
C602280045	---	1	22	23,7	80	40	32	16	24
C602280050	---	1	24	27,7	88	44	36	18	28
C602280055	---	1	27	31,6	100	50	40	20	32
C602280060	---	1	30	35,6	108	54	44	22	36



### Rhomboidal plug for T slot

Rhomboidal plug for T slot, in hardening and tempering steels, No 510 class 8.8.




Code	€	M	D (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602300005	---	10	11,7	18	14	7	12
C602300010	---	10	13,7	22	16	8	14
C602300015	---	10	17,7	28	20	10	18
C602300020	---	12	13,7	22	16	8	14
C602300025	---	14	15,7	25	18	9	16
C602300030	---	16	17,7	28	20	10	18
C602300035	---	16	19,7	32	24	12	20

Code	€	M	D (mm)	A (mm)	B (mm)	C (mm)	Cave (mm)
C602300040	---	16	21,7	35	28	14	22
C602300045	---	16	27,7	44	36	18	28
C602300050	---	18	19,7	32	24	12	20
C602300055	---	20	21,7	35	28	14	22
C602300060	---	24	27,7	44	36	18	28
C602300065	---	30	35,6	54	44	22	36



### Normal polished washers

Normal polished washers, in automatic hardening and tempering steels.



Code	€	Pz.	For thread	D (mm)	E (mm)	H (mm)
C602350060	---	10	M6	6,6	13	3,5
C602350080	---	10	M8	8,4	18	4
C602350100	---	10	M10	10,5	22	4
C602350120	---	10	M12	13	28	5
C602350140	---	10	M14	15	35	6
C602350160	---	10	M16	17	35	6
C602350180	---	10	M18	19	40	6
C602350200	---	10	M20	21	40	6

Code	€	Pz.	For thread	D (mm)	E (mm)	H (mm)
C602350220	---	10	M22	23	45	8
C602350240	---	10	M24	25	45	8
C602350270	---	1	M27	28	60	10
C602350300	---	1	M30	31	60	10
C602350360	---	1	M36	37	70	12
C602350420	---	1	M42	43	80	12
C602350480	---	1	M48	49	90	12