



Digital micrometer for external use, protection level IP 54

Digital micrometer with LCD display, **IP 54 protection level**, hard metal measuring faces, steel frame with insulating plates, locknut, friction thimble, precision according to internal standard.

Electronic features:

- ON/OFF switch,
- automatic switch-off,
- re-set in any position,
- mm/inch reading,



Battery code . F030270357.

Code	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Stem ø (mm)	Screw pitch (mm)	Data exit
F100700010	◆	25÷50	0,001	0,006	6	6,5	0,5	no
F100700015	◆	50÷75	0,001	0,007	6	6,5	0,5	no
F100700020	◆	75÷100	0,001	0,007	6	6,5	0,5	no
F100700025	◆	100÷125	0,001	0,008	6	6,5	0,5	no
F100700030	◇	125÷150	0,001	0,008	6	6,5	0,5	no
F100700035	◇	150÷175	0,001	0,009	6	6,5	0,5	no
F100700040	◇	175÷200	0,001	0,009	6	6,5	0,5	no



Digital micrometer for external use, protection level IP 65 with integrated wireless

Digital micrometer **with wireless transmission integrated**, with liquid crystal display, **degree of protection IP 65**, steel rods tempered and ground with contact surfaces in hard metal, steel structure with insulating rivets, clutch built into the drum, accuracy according to internal standards.

Electronic functions:

- on / off switch
- QuickStart electronics
- QuickLock function
- reset in each position
- ABS system (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- mm / inch switching

Battery cod. F030272032

i-Stick USB receiver with integrated wireless cod. F054950005



integrated
iW wireless



Code	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Stem ø (mm)	Screw pitch (mm)	Data exit
F108600025	◇	0÷25	0,001	0,002	10	6,5	0,5	yes
F108600050	◇	25÷50	0,001	0,002	10	6,5	0,5	yes
F108600075	◇	50÷75	0,001	0,003	10	6,5	0,5	yes
F108600100	◇	75÷100	0,001	0,003	10	6,5	0,5	yes



Digital micrometer for external use, protection level IP 40

Digital micrometer with liquid crystal display, **degree of protection IP40**, steel rods tempered and ground with contact surfaces in hard metal, steel structure with insulating rivets, clutch incorporated in the drum.

Electronic functions:

- on / off switch
- QuickStart electronics
- QuickLock function
- zeroing in each position
- mm / inch switching

Battery cod. F030272032



Code	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Stem ø (mm)	Screw pitch (mm)	barrel ø (mm)	Data exit
F108300025	◆	0÷25	0,001	0,002	10	6,5	0,5	21	no