



Digital micrometric head

Micrometric head, contact surface in hard metal, matt chromium-plated vernier, steel structure, precision according to DIN 863/2.



Code	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Stem ø (mm)	Coupling ø (mm)	barrel ø (mm)	Description
F108550005	↘	0÷6,5	0,01	0,003	3,5	6	9,5	without clutch
F108550010	↘	0÷13	0,01	0,003	6,5	9,5	13,5	without clutch
F108550015	↘	0÷25	0,01	0,003	6,5	12	18	with clutch
F108550020	↘	0÷25	0,01	0,003	8	12	18	with clutch, stem without rotation



Digital micrometer for internal use with 3 tips, protection level IP 52

Digital micrometer for internal measurement with 3 points with liquid crystal display, **IP 52 protection degree**, contact surfaces in steel, with carbide insert from the measuring range of 12-16 mm, steel structure, adjustment of the measuring force by means of budjet lock, for through holes; from the measuring range of 12-16 mm also for blind holes, precision according to DIN 863/4. **Supplied with calibration ring.**

Electronic functions:

- on / off switch
- QuickLock function
- system **ABS** (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- zero position in each position
- mm / inch switching

Interface data output with systems:

- RS 232 cable cod. F038430005
- Digimatic cable cod. F038430010
- USB cable cod. F038430015
- Battery cod. F030272032



Code	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Max depth (mm)	Data exit
F108400005	↘	6÷8	0,001	0,004	8,5	58	yes
F108400010	↘	8÷10	0,001	0,004	8,5	58	yes
F108400015	↘	10÷12	0,001	0,004	8,5	58	yes
F108400020	↘	12÷16	0,001	0,004	8,5	64	yes
F108400025	↘	16÷20	0,001	0,004	8,5	64	yes
F108400030	↘	20÷25	0,001	0,004	8,5	68	yes
F108400035	↘	25÷30	0,001	0,004	8,5	68	yes
F108400040	↘	30÷40	0,001	0,004	8,5	76	yes
F108400045	↘	40÷50	0,001	0,004	8,5	76	yes
F108400050	↘	50÷60	0,001	0,005	8,5	79	yes
F108400055	↘	60÷70	0,001	0,005	8,5	79	yes
F108400060	↘	70÷85	0,001	0,005	8,5	97	yes
F108400065	↘	85÷100	0,001	0,005	8,5	97	yes
F108400070	↘	100÷125	0,001	0,006	8,5	132	yes
F108400075	↘	125÷150	0,001	0,006	8,5	132	yes
F108400080	↘	150÷175	0,001	0,007	8,5	132	yes
F108400085	↘	175÷200	0,001	0,007	8,5	132	yes



Set of digital micrometer for internal use with 3 tips, protection level IP 52

Set of digital micrometers for internal measurement with 3 points with liquid crystal display, **degree of protection IP 52**, contact surfaces in steel, with carbide insert from the measuring range of 12-16 mm, steel structure, adjustment of the measuring force by means of budjet lock, for through holes; from the measuring range of 12-16 mm also for blind holes, precision according to DIN 863/4. **Supplied with calibration ring.**



Electronic functions:

- on / off switch
- QuickLock function
- system **ABS** (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- zero position in each position
- mm / inch switching

Interface data output with systems:

- RS 232 cable cod. F038430005
- Digimatic cable cod. F038430010
- USB cable cod. F038430015

Battery cod. F030272032



Code	€	Measurement field (mm)	No. of heads
F108409005	↘	6÷12	3
F108409010	↘	12÷20	2

Code	€	Measurement field (mm)	No. of heads
F108409015	↘	20÷50	4
F108409020	↘	50÷100	4