



Comparator support with granite top

Comparator support with granite top DIN 876/00, ground and finely lapped, with rigid arm or double arm, mounting hole \varnothing 8 mm.

F30516 - without micrometric adjustment,

F30517 - with micrometric adjustment,

F30437 - with micrometric adjustment and mobile horizontal arm



F30516



F30517



F30437



Final Code	F30516	F30517	F30437	Table dimensions (mm)	Radius of action (mm)	Max measurable height (mm)	Column \varnothing (mm)	Execution	Cross arm \varnothing (mm)
0200	€	€	€	165x100	60	180	22	Fixed horizontal arm	-
0250	€	€	€	250x200	120	210	35	Fixed horizontal arm	-
0250	€	€	€	250x200	200	230	35	Mobile horizontal arm	22



Control desk for control of concentricity



Control bench for concentricity, roundness and parallelism verification. Precision ground support surface, with flatness in compliance with DIN 876/2, side "T" slot for comparator holder stand with micrometric adjustment for comparator with locking shank \varnothing 8 mm tolerance h 6. Two sliding supports for tailstocks, left tailstock with fixed point, right one with mobile spring point, stroke approx. 15 mm for quick positioning of the piece. Tailstocks fixed with closing bush and cam.



Code	€	Tips height (mm)	Piece maximum length (mm)	Base dimensions (mm)	Width cava T (mm)
F503170005	€	50	200	350x110	10
F503170010	€	50	350	500x110	10
F503170015	€	75*	200	350x110	10

Code	€	Tips height (mm)	Piece maximum length (mm)	Base dimensions (mm)	Width cava T (mm)
F503170020	€	75*	350	500x110	10
F503170025	€	100	450	700x180	12
F503170030	€	150	450	700x180	12

*Supplied with a 90° "V" housing for the tailstock supports in the upper part, to support pieces of up to \varnothing 20 mm.



Supports with V-shaped grooves

Hardened supports with V groove, they are placed onto the bench plate instead of the tailstocks. Delivered in pairs



Code	€	Height (mm)	Support \varnothing (mm)	Width cava T (mm)
F304100005	€	65	5-25	10
F304100010	€	100	5-50	12



Supports with rollers

Supports with rollers axial coaxial line tolerance of 0.005 mm, they are placed onto the bench plate instead of the tailstocks. Supplied in pairs.



Code	€	Height (mm)	Support \varnothing (mm)	Width cava T (mm)
F304150005	€	65	3-30	10
F304150010	€	100	4-60	12

