

Abrasive corundum strip wheel

Strip wheel in abrasive corundum canvas, with strips fixed in radial fan.
Use in grinding, polishing and finishing of flat and contoured pieces, corners and also in situations of difficult access.
For machining of alloy steel and other.



Code	€	Dimensions øxH (mm)	Bore ø (mm)	Grain	Max revolutions no. (rev/min)
L357051606	◆	165x50	54	60	4.600
L357051608	◆	165x50	54	80	4.600
L357051612	◆	165x50	54	120	4.600
L357051618	◆	165x50	54	180	4.600
L357052006	◆	200x50	54	60	3.800
L357052008	◆	200x50	54	80	3.800

Codice	Alluminio e leghe	Acciaio	Ghisa	Plastiche e Legno
L35705	○	●	○	●



Code	€	Dimensions øxH (mm)	Bore ø (mm)	Grain	Max revolutions no. (rev/min)
L357052012	◆	200x50	54	120	3.800
L357052018	◆	200x50	54	180	3.800
L357052506	◆	250x50	100	60	3.800
L357052508	◆	250x50	100	80	3.800
L357052512	◆	250x50	100	120	3.800
L357052518	◆	250x50	100	180	3.800

Locking flange for strip wheels

Pair of locking flanges for abrasive strip wheels. The bore diameter must be modified as required.



Code	€	ø (mm)	For wheels ø (mm)
L357060300	◆	84/54	165-200
L357060100	◆	130/100	250




Grinding wheel with cylindrical stem

Cylindrical grinding wheel with steel stem, made of pink corundone and vitrified ceramic binder, suitable for universal use on all types of steel and cast iron.



Code	€	Pz.	Dimensions øxH (mm)	Pivot ø (mm)	Suggested no. of revolutions (rev/min)	Specification
L401000306	◆	25	3x6	3	90.000	40A100-RV
L401000406	◆	25	4x6	3	80.000	40A100-RV
L401000510	◆	25	5x10	3	73.000	40A100-RV
L401000610	◆	25	6x10	3	61.000	40A80-RV
L401000611	◆	25	6x10	6	61.000	40A80-RV
L401000613	◆	25	6x13	3	54.000	40A80-RV
L401000810	◆	25	8x10	3	61.000	40A80-RV
L401000813	◆	25	8x13	3	54.000	40A80-RV
L401000820	◆	25	8x20	6	41.000	40A80-RV
L401001013	◆	25	10x13	6	54.000	40A80-RV
L401001020	◆	25	10x20	6	41.000	40A80-RV
L401001320	◆	25	13x20	6	48.000	40A60-RV

Codice	Acciaio	Ghisa
L40100	●	●



Code	€	Pz.	Dimensions øxH (mm)	Pivot ø (mm)	Suggested no. of revolutions (rev/min)	Specification
L401001620	◆	25	16x20	6	47.000	40A60-RV
L401001621	◆	25	16x20	6	47.000	40A46-RV
L401001625	◆	25	16x25	6	35.000	40A60-RV
L401002020	◆	25	20x20	6	42.000	40A60-RV
L401002021	◆	25	20x20	6	42.000	40A46-RV
L401002030	◆	25	20x30	6	30.000	40A46-RV
L401002031	◆	25	20x30	6	30.000	40A60-RV
L401002525	◆	25	25x25	6	25.000	40A46-PV
L401003030	◆	25	30x30	6	17.000	40A46-PV
L401004025	◆	25	40x25	6	19.000	40A46-PV
L401004040	◆	25	40x40	6	12.000	40A60-PV