




### Grinding wheel with cylindrical stem

Cylindrical grinding wheel with stem, ZY shape, dark red and white ADW high grade corundum abrasive with ceramic binder, hardness degree M, high attack, block-resistant, in particular suitable for alloy steels and non-alloy steels, high-speed steels and stainless steel, fusion of steel and cast iron and non-ferrous metals. The best performance is obtained with a peripheral speed of 20 to 30 m/s.

Codice

Alluminio e leghe  
 Acciaio  
 Acciaio INOX  
 Ghisa

L40117 ÷ L40127



Final Code	L40117		L40119		L40121		L40123		L40125		L40127		Dimensions øxH (mm)	Pivot ø (mm)	Max no. of revolutions (rev/min)
	GRAIN 24	Pz.	GRAIN 30	Pz.	GRAIN 46	Pz.	GRAIN 60	Pz.	GRAIN 80	Pz.	GRAIN 100	Pz.			
0408												10	4x8	3	175.000
0409												10	4x8	6	177.000
0510												10	5x10	3	130.000
0613												10	6x13	3	93.000
0614												10	6x13	6	131.000
0810												10	8x10	3	87.000
0811												10	8x10	6	119.000
0816												10	8x16	3	61.000
0817												10	8x16	6	119.000
1013												10	10x13	3	58.000
1014												10	10x13	6	95.000
1020												10	10x20	6	95.000
1025												10	10x25	6	83.000
1032												10	10x32	6	83.000
1303												10	13x3	3	73.000
1313												10	13x13	6	73.000
1320												10	13x20	6	73.000
1325												10	13x25	6	73.000
1604												10	16x4	6	59.000
1620												10	16x20	6	59.000
1632												10	16x32	6	51.000
2006												10	20x6	6	47.000
2020												10	20x20	6	47.000
2025												10	20x25	6	47.000
2032												10	20x32	6	41.000
2040												10	20x40	6	32.000
2506												10	25x6	6	38.000
2525												10	25x25	6	38.000
2532												10	25x32	6	32.000
3208												5	32x8	6	29.000
3220												5	32x20	6	29.000
3232												5	32x32	6	25.000
3240												5	32x40	6	18.000
4010												5	40x10	6	23.000
4040												5	40x40	6	16.000

ABRASIVE ROLLERS  
GRINDING POINTS




### Grinding wheel with ball stem

Cylindrical grinding wheel with stem, KU ball shape, pink AR high grade corundum, hardness degree O with ceramic binder, keeps profile, resistant on borders. Especially suitable for alloy and non-alloy steels, high speed steels, stainless steels and fusions of steel and cast iron. The best performance is obtained with a peripheral speed of 25 to 40 m/s for use on edges and from 15 to 25 m/s on flat surfaces.

Codice

Acciaio  
 Acciaio INOX  
 Ghisa

L40151 ÷ L40157



Final Code	L40151		L40153		L40155		L40157		Ø (mm)	Pivot ø (mm)	Max no. of revolutions (rev/min)
	GRAIN 46	Pz.	GRAIN 60	Pz.	GRAIN 80	Pz.	GRAIN 100	Pz.			
0030									3	3	300.000
0050									5	3	190.000
0080									8	3	116.000
0081									8	6	119.000
0100									10	3	83.000
0101									10	6	95.000
0130									13	3	54.000
0131									13	6	73.000
0160									16	6	59.000
0250									25	6	38.000

● Recommended ● Suitable ○ Possible

◆ Available from stock CDU ◇ Shipping from external warehouse