



Polishing paste block

Polishing paste blocks that can be used with felt with stems and felt or cloth discs, the colors of the paste identify the various uses.



Code	€	Type	Colour	Execution	Use per	Dimensions (mm)
L40090005	---	PP 1 VP FE	green	Pre-polishing	steel + stainless steel	70x50x140
L400900010	---	PP 2 VP MS	grey	Pre-polishing	aluminum + brass	70x50x140
L400900015	---	PP 3 VP NE	brown	Pre-polishing	non-ferrous metals	70x50x140
L400900020	---	PP 4 HGP	pink	Mirror polishing	all metals	70x50x140
L400900025	---	PP 5 HGP K	beige	Mirror polishing	synthetic materials	70x50x140



Grinding pastes

Oil-based grinding paste, aggressive SiC abrasive, to be used for finishing operations and during the preparation for polishing by means of felt grinding wheels and cloth discs.



Code	€	Grain	Type	Content (g)
L400950005	---	90	SFP	250
L400950010	---	150	SFP	250
L400950015	---	280	SFP	250

Code	€	Grain	Type	Content (g)
L400950020	---	360	SFP	250
L400950025	---	600	SFP	250
L400950030	---	800	SFP	250

GRINDING POINTS



Poliflex grinding wheel with cylindrical stem

Cylindrical Poliflex wheel with shank, ZY shape, GR type soft binder with pink AR corundum (AR). Preparation for polishing and silk finishing. Finishing, polishing and pre-working on steels, stainless steels; satin finishing on aluminium alloys; gloss finishing on bronze, brass and copper.

Codice Acciaio Acciaio INOX Ghisa

L40215 ÷ L40220



Final Code	L40215		L40220		Dimensions øxH (mm)	Pivot ø (mm)	Suggested no. of revolutions (rev/min)
	GRAIN 120	Pz.	GRAIN 220	Pz.			
0408	---	10			4x8	3	47.000
0610	---	10			6x10	3	32.000
0808	---	10	---	10	8x8	3	24.000
0812	---	10	---	10	8x12	3	24.000
1006	---	10			10x6	3	19.000
1010	---	10	---	10	10x10	3	19.000
1011	---	10			10x10	6	19.000
1015	---	10	---	10	10x15	3	19.000
1016	---	10	---	10	10x15	6	19.000
1025	---	10	---	10	10x25	6	19.000
1208	---	10			12x8	3	16.000
1209	---	10			12x8	6	16.000
1212	---	10			12x12	3	16.000
1213	---	10			12x12	6	16.000

Final Code	L40215		L40220		Dimensions øxH (mm)	Pivot ø (mm)	Suggested no. of revolutions (rev/min)
	GRAIN 120	Pz.	GRAIN 220	Pz.			
1220	---	10			12x20	3	16.000
1221	---	10	---	10	12x20	6	16.000
1515	---	10			15x15	6	12.000
1525	---	10	---	10	15x25	6	12.000
1530	---	10	---	10	15x30	6	12.000
2012	---	10			20x12	6	9.500
2020	---	10	---	10	20x20	6	9.500
2030	---	10			20x30	6	9.500
2515	---	10			25x15	6	7.500
2525	---	10	---	10	25x25	6	7.500
3020	---	5			30x20	6	6.500
3030	---	5			30x30	6	6.500
4025	---	5			40x25	8	4.500



Poliflex grinding wheel with ball stem

Poliflex wheel with shank, KU ball shape, GR type soft binder with pink AR corundum (AR). Preparation for polishing and silk finishing. Finishing, polishing and pre-working on steels, stainless steels; satin finishing on aluminium alloys; gloss finishing on bronze, brass and copper.



Codice Acciaio Acciaio INOX Ghisa

L40310



Code	€	Pz.	ø (mm)	Pivot ø (mm)	Suggested no. of revolutions (rev/min)	Grain
L403100080	---	10	8	3	24.000	120
L403100100	---	10	10	3	19.000	120
L403100120	---	10	12	6	16.000	120
L403100150	---	10	15	6	12.000	120

Code	€	Pz.	ø (mm)	Pivot ø (mm)	Suggested no. of revolutions (rev/min)	Grain
L403100200	---	10	20	6	9.500	120
L403100250	---	10	25	6	7.500	120
L403100300	---	5	30	6	6.500	120

● Recommended ● Suitable ○ Possible

◆ Available from stock CDU ◇ Shipping from external warehouse