



Reversible lever ratchet

Reversible ratchet with sealed mechanism; onnection 3/8 "UNI 3315 DIN 3122; 72 teeth model with 5 ° recovery angle; lever inversion system that can be used with one hand; usable with two hands during the maneuver, keeping the ratchet head pressed against the screw; ergonomic head in forged steel in a single body, ergonomic conical handle in two-component plastic material for a comfortable and secure grip; hooking slot on the handle to be able to hang it on a tool panel, forged steel body with "double T" section, chromed execution.



Code	€	Overall length (mm)	
N101220005	-,	210	



Reversible ratchet certified IP51

Reversible ratchet with 3/8 "UNI 3315 DIN 3122, model 72 teeth with 5° angle of view, ring inversion system, sealed with IP51 protection mechanism, new patented pawl with greater resistance, forged steel body with section a double T, lightness and resistance to bending, conical bimaterial grip to ensure a perfect and safe grip, the coupling slot on the handle for hanging the ratchet to the toolholder panel, chrome execution.



Code	€	Overall length (mm)	
N103420005	-,	180	



Simple ratchet without sliding frame

Simple ratchet with 3/8" connection UNI 3315 DIN 3122, model with 60 teeth with recovery angle of 6°, inversion ring nut system with sliding frame, ergonomic grip in bi-component plastic material, body in chrome vanadium steel, chrome-plated execution. Suitable for operation in restricted spaces.



Code	€	Overall length (mm)	
N101250005	-,	181	

T lever with sliding square connection

N10131 - T lever with sliding square 3/8" connection UNI 3315 DIN 3122, in chrome vanadium steel, chrome execution.

N10130 - T lever with sliding square 3/8" connection UNI 3315 DIN 3122, in chrome vanadium steel, polished chrome execution.



3/8



Extension

N10136 - Extension 3/8" connection UNI 3316 DIN 3123, in chrome vanadium steel, chrome execution.

N10135 - Extension 3/8" connection UNI 3316 DIN 3123, in chrome vanadium steel, polished chrome execution.





Final Code	N10136	N10135	Pz.	Overall length (mm)	
0075		-,	5	75	
0125	- , ♦ 1	-,	5	125	
0250	- , ♦ 1	-,	5	250	