



Digital depth gauge, protection level IP 67 with integrated wireless

Digital depth gauge **with integrated wireless transmission**, with liquid crystal display, **degree of protection IP 67**, housing key and operation with excellent chemical resistance to fluids and cooling lubricants, structure in tempered stainless steel, ground contact surfaces, contact bolt \varnothing 1.5 mm, upper locking screw, precision according to DIN 862.

Electronic functions:

- on / off switch
- QuickStart electronics - QuickLock function
- zeroing in each position
- preset value (+/- Preset function)
- mm / inch switching



integrated IW wireless

DIN 862
INOX
IP 67
↻
➔
integrated IW wireless
Conversione mm"/"
📱

Battery cod. F030272032

i-Stick USB receiver with integrated wireless cod. F054950005

F05219	€	Measurement field (mm)	Figures height (mm)	Bridge length (mm)	Resolution (mm)	Error limit (mm)	Data exit
F052190150	---	0±150	11	100	0,01	0,03	yes
F052190200	---	0±200	11	100	0,01	0,03	yes
F052190300	---	0±300	11	150	0,01	0,04	yes
F052190500	---	0±500	11	150	0,01	0,05	yes



Digital micrometer for external use, protection level IP 54

Digital micrometer with LCD display, **IP 54 protection level**, hard metal measuring faces, steel frame with insulating plates, locknut, friction thimble, precision according to standard DIN 863/1.

Electronic features]

- ON/OFF switch,
- automatic switch-off,
- re-set in any position,
- mm/inch reading,



DIN 863/1
IP 54
Conversione mm"/"
📱

Battery code . F030270357

F10710	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Stem \varnothing (mm)	Screw pitch (mm)	Data exit
F107100005	---	0±25	0,001	0,006	6	6,5	0,5	no



Digital micrometer for external use, protection level IP 65 with integrated wireless

Digital micrometer **with wireless transmission integrated**, with liquid crystal display, **degree of protection IP 65**, steel rods tempered and ground with contact surfaces in hard metal, steel structure with insulating rivets, clutch built into the drum, accuracy according to internal standards.

Electronic functions:

- on / off switch
- QuickStart electronics
- QuickLock function
- reset in each position
- ABS system (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- mm / inch switching



integrated IW wireless

Norma interna
IP 65
↻
➔
integrated IW wireless
Conversione mm"/"
📱

Battery cod. F030272032

i-Stick USB receiver with integrated wireless cod. F054950005

F10860	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Stem \varnothing (mm)	Screw pitch (mm)	Data exit
F108600025	---	0±25	0,001	0,002	10	6,5	0,5	yes
F108600050	---	25±50	0,001	0,002	10	6,5	0,5	yes
F108600075	---	50±75	0,001	0,003	10	6,5	0,5	yes
F108600100	---	75±100	0,001	0,003	10	6,5	0,5	yes