



Set of digital micrometer for internal use with 3 tips, protection level IP 52

Set of digital micrometers for internal measurement with 3 points with liquid crystal display, **degree of protection IP 52**, contact surfaces in steel, with carbide insert from the measuring range of 12-16 mm, steel structure, adjustment of the measuring force by means of budget lock, for through holes; from the measuring range of 12-16 mm also for blind holes, precision according to DIN 863/4. **Supplied with certified calibration ring.**

Electronic functions:

- on / off switch
- QuickLock function
- system **ABS** (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- zero position in each position
- mm / inch switching

Interface data output with systems:

- RS 232 cable cod. F038430005
- Digimatic cable cod. F038430010
- USB cable cod. F038430015
- Battery cod. F030272032



DIN 863/4
IP52
RS232
Digimatic
USB
Conversion mm/"

F10840	€	Measurement field (mm)	No. of heads
F108409005	---	6÷12	3
F108409010	---	12÷20	2

F10840	€	Measurement field (mm)	No. of heads
F108409015	---	20÷50	4
F108409020	---	50÷100	4



Micrometer for internal use with 3 tips with lever

Micrometer for internal measurement with 3 points, with lever handle, contact surfaces in steel, with carbide insert from the measuring range of 12-16 mm, steel structure, for through holes; from the measuring range of 12 mm also for blind holes. **Supplied with certified calibration ring.**

On request recommended digital comparator device with the highest possible resolution.



F10845	€	Measurement field (mm)	Max depth (mm)
F108450005	---	6÷8	58
F108450010	---	8÷10	58
F108450015	---	10÷12	58
F108450020	---	12÷16	64
F108450025	---	16÷20	64
F108450030	---	20÷25	68
F108450035	---	25÷30	68
F108450040	---	30÷40	76
F108450045	---	40÷50	76

F10845	€	Measurement field (mm)	Max depth (mm)
F108450050	---	50÷60	79
F108450055	---	60÷70	79
F108450060	---	70÷85	97
F108450065	---	85÷100	97
F108450070	---	100÷125	132
F108450075	---	125÷150	132
F108450080	---	150÷175	132
F108450085	---	175÷200	132



Set of micrometer for internal use with 3 tips with lever

Set of micrometers for internal measurement with 3 points, with lever handle, contact surfaces in steel, with carbide insert from the measuring range of 12-16 mm, steel structure, for through holes; from the measuring range of 12 mm also for blind holes. **Supplied with certified calibration ring.**

On request recommended digital indicator (comparator) device with the highest possible resolution.



F10845	€	Measurement field (mm)	No. of heads
F108459005	---	6÷12	3
F108459010	---	12÷20	2
F108459015	---	20÷50	4
F108459020	---	50÷100	4