



Digital depth gauge, protection level IP 67 with integrated wireless

Digital depth gauge **with integrated wireless transmission**, with liquid crystal display, **degree of protection IP 67**, housing key and operation with excellent chemical resistance to fluids and cooling lubricants, structure in tempered stainless steel, ground contact surfaces, contact bolt $\varnothing$ 1.5 mm, upper lockin screw, precision according to DIN 862.

Electronic functions:

- on / off switch
- QuickStart electronics - QuickLock function
- zeroing in each position
- preset value (+/- Preset function)
- mm / inch switching



integrated
IW wireless



Battery cod. F030272032

i-Stick USB receiver with integrated wireless cod. F054950005

F05219	€	Measurement field (mm)	Figures height (mm)	Bridge length (mm)	Resolution (mm)	Error limit (mm)	Data exit
F052190150	---	0÷150	11	100	0,01	0,03	yes
F052190200	---	0÷200	11	100	0,01	0,03	yes
F052190300	---	0÷300	11	150	0,01	0,04	yes
F052190500	---	0÷500	11	150	0,01	0,05	yes



Digital micrometer for external use, protection level IP 65 with integrated wireless

Digital micrometer **with wireless transmission integrated**, with liquid crystal display, **degree of protection IP 65**, steel rods tempered and ground with contact surfaces in hard metal, steel structure with insulating rivets, clutch built into the drum, accuracy according to internal standards.

Electronic functions:

- on / off switch
- QuickStart electronics
- QuickLock function
- reset in each position
- ABS system (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- mm / inch switching



integrated
IW wireless



Battery cod. F030272032

i-Stick USB receiver with integrated wireless cod. F054950005

F10860	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Stem $\varnothing$ (mm)	Screw pitch (mm)	Data exit
F108600025	---	0÷25	0,001	0,002	10	6,5	0,5	yes
F108600050	---	25÷50	0,001	0,002	10	6,5	0,5	yes
F108600075	---	50÷75	0,001	0,003	10	6,5	0,5	yes
F108600100	---	75÷100	0,001	0,003	10	6,5	0,5	yes



Digital micrometer for external use, protection level IP 40

Digital micrometer with liquid crystal display, **degree of protection IP40**, steel rods tempered and ground with contact surfaces in hard metal, steel structure with insulating rivets, clutch incorporated in the drum.



Electronic functions:

- on / off switch
- QuickStart electronics
- QuickLock function
- zeroing in each position
- mm / inch switching

Battery cod. F030272032



F10830	€	Measurement field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Stem $\varnothing$ (mm)	Screw pitch (mm)	barrel $\varnothing$ (mm)	Data exit
F108300025	---	0÷25	0,001	0,002	10	6,5	0,5	21	no