



Digital micrometer for internal use with 3 tips, protection level IP 52

Digital micrometer for internal measurement with 3 points with liquid crystal display, **IP 52 protection degree**, contact surfaces in steel, with carbide insert from the measuring range of 12-16 mm, steel structure, adjustment of the measuring force by means of budget lock, for through holes; from the measuring range of 12-16 mm also for blind holes, precision according to DIN 863/4. **Supplied with calibration ring.**

Electronic functions:

- on / off switch
- QuickLock function
- system **ABS** (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- zero position in each position
- mm / inch switching

Interface data output with systems:

- RS 232 cable cod. F038430005
- Digimatic cable cod. F038430010
- USB cable cod. F038430015
- Battery cod. F030272032



F10840	€	Measure ment field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Max depth (mm)	Data exit
F108400005	-,-	6±8	0,001	0,004	8,5	58	yes
F108400010	-,-	8±10	0,001	0,004	8,5	58	yes
F108400015	-,-	10±12	0,001	0,004	8,5	58	yes
F108400020	-,-	12±16	0,001	0,004	8,5	64	yes
F108400025	-,-	16±20	0,001	0,004	8,5	64	yes
F108400030	-,-	20±25	0,001	0,004	8,5	68	yes
F108400035	-,-	25±30	0,001	0,004	8,5	68	yes
F108400040	-,-	30±40	0,001	0,004	8,5	76	yes
F108400045	-,-	40±50	0,001	0,004	8,5	76	yes

F10840	€	Measure ment field (mm)	Resolution (mm)	Error limit (mm)	Figures height (mm)	Max depth (mm)	Data exit
F108400050	-,-	50±60	0,001	0,005	8,5	79	yes
F108400055	-,-	60±70	0,001	0,005	8,5	79	yes
F108400060	-,-	70±85	0,001	0,005	8,5	97	yes
F108400065	-,-	85±100	0,001	0,005	8,5	97	yes
F108400070	-,-	100±125	0,001	0,006	8,5	132	yes
F108400075	-,-	125±150	0,001	0,006	8,5	132	yes
F108400080	-,-	150±175	0,001	0,007	8,5	132	yes
F108400085	-,-	175±200	0,001	0,007	8,5	132	yes



Set of digital micrometer for internal use with 3 tips, protection level IP 52

Set of digital micrometers for internal measurement with 3 points with liquid crystal display, **degree of protection IP 52**, contact surfaces in steel, with carbide insert from the measuring range of 12-16 mm, steel structure, adjustment of the measuring force by means of budget lock, for through holes; from the measuring range of 12-16 mm also for blind holes, precision according to DIN 863/4. **Supplied with calibration ring.**

Electronic functions:

- on / off switch
- QuickLock function
- system **ABS** (display can be set to zero without losing the preset value reference)
- value preset (+/- Preset function)
- zero position in each position
- mm / inch switching

Interface data output with systems:

- RS 232 cable cod. F038430005
- Digimatic cable cod. F038430010
- USB cable cod. F038430015
- Battery cod. F030272032



F10840	€	Measurement field (mm)	No. of heads
F108409005	-,-	6±12	3
F108409010	-,-	12±20	2

F10840	€	Measurement field (mm)	No. of heads
F108409015	-,-	20±50	4
F108409020	-,-	50±100	4