


## format professional quality **Appoggio a vite**

Appoggio a vite regolabile, in acciaio da bonifica verniciato.



Codice	€	h-min (mm)	H-max (mm)	TR (mm)	ø D2 (mm)	ø D1 (mm)	Forza Max (kN)
C609290052	---	42	52	30x4	50	50	100
C609290070	---	50	70	30x4	50	50	100
C609290100	---	70	100	30x4	50	50	100



Codice	€	h-min (mm)	H-max (mm)	TR (mm)	ø D2 (mm)	ø D1 (mm)	Forza Max (kN)
C609290140	---	100	140	40x7	68	68	120
C609290200	---	140	210	50x8	80	70	170





## Appoggio a vite

Appoggi a vite regolabile, in acciaio da bonifica verniciato, **Nr. 6400**.



Codice	€	H min (mm)	H max (mm)	d (mm)	D (mm)	Forza max (kN)
C600100038	---	40 <sup>1)</sup>	50	34	34	20
C600100050	---	54	70	50	50	60
C600100070	---	73	100	50	50	60

<sup>1)</sup>Senza foro.



Codice	€	H min (mm)	H max (mm)	d (mm)	D (mm)	Forza max (kN)
C600100100	---	100	140	65	70	105
C600100140	---	140	210	70	80	180
C600100190	---	190	300	80	100	360




## Prolunga per appoggi a vite

Prolunghe per appoggi a vite che permettono l'allungamento dell'altezza dell'appoggio, in acciaio da bonifica verniciato.



Codice	€	D (mm)	h (mm)
C600150005	---	35	25
C600150010	---	35	50
C600150015	---	35	75
C600150020	---	35	100
C600150025	---	50	50
C600150030	---	50	75



Codice	€	D (mm)	h (mm)
C600150035	---	50	100
C600150040	---	50	150
C600150045	---	70	50
C600150050	---	70	100
C600150055	---	70	150
C600150060	---	70	200




## Appoggio a vite con base in alluminio

Appoggi a vite con base in lega di alluminio "ERGAL", regolabili con possibilità di posizionamento e registrazione sia in verticale che orizzontale, **Nr. 6401**.



Codice	€	H min (mm)	H max (mm)	d (mm)	D (mm)	Forza max (kN)
C600180042	---	45	55	50	50	30
C600180060	---	55	70	50	50	30



Codice	€	H min (mm)	H max (mm)	d (mm)	D (mm)	Forza max (kN)
C600180070	---	73	103	50	50	30