

**CENTRO DISTRIBUZIONE UTENSILI S.p.a.****CUT OIL F500**

Revision nr. 8
Dated 08/05/2024
Printed on 09/05/2024
Page n. 1/15
Replaced revision:7 (Dated: 06/09/2022)

EN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: U05140
Product name: CUT OIL F500
UFI: C3N0-D0CT-E004-FN2W

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Universal cutting fluid.
Uses advised against: Different uses than those intended.

1.3. Details of the supplier of the safety data sheet

Name: CENTRO DISTRIBUZIONE UTENSILI S.p.a.
Full address: Via delle Gerole, 19
District and Country: 20867 CAPONAGO (MB)
ITALY
tel. +39 02 95746081
fax. + 39 02 95745182

e-mail address of the competent person

responsible for the Safety Data Sheet: info@cdu.net
Supplier: CENTRO DISTRIBUZIONE UTENSILI S.p.a.

1.4. Emergency telephone number

For urgent inquiries refer to: CENTRO DISTRIBUZIONE UTENSILI S.p.a. +39 02 95746081
(Technical support - Office hour 8.30-13.00 - 14.00-17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: DANGER

Hazard statements:

H222: Extremely flammable aerosol.
H229: Pressurised container: may burst if heated.



EUH066
EUH208

Repeated exposure may cause skin dryness or cracking.
Contains: N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (Mixture).
May produce an allergic reaction.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P102 Keep out of reach of children.
P211 Do not spray on an open flame or other ignition source.

Contains: HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC.

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CLP.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.
The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	X = Conc. %	Classification (EC) 1272/2008 (CLP)
----------------	-------------	-------------------------------------

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

INDEX 649-474-00-6	$20 \leq x < 40$	Classification note according to Annex VI to the CLP Regulation: L. Substance with extract content in DMSO of less than 3% by weight, determined using the IP 346 method.
EC 265-169-7		
CAS 64742-65-0		
REACH Reg. 01-2119471299-27		

PROPANE

INDEX 601-003-00-5	$18,2 \leq x < 23,2$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
CAS 74-98-6		
REACH Reg. 01-2119486944-21		

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

INDEX -	$7,3 \leq x < 12,3$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066
EC 919-857-5		
CAS -		
REACH Reg. 01-2119463258-33		

BUTANE

INDEX 601-004-00-0	$8,4 \leq x < 10,4$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7		
CAS 106-97-8		
REACH Reg. 01-2119474691-32		

ISOBUTANE

INDEX 601-004-00-0	$3,1 \leq x < 5,1$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 200-857-2		
CAS 75-28-5		
REACH Reg. 01-2119485395-27		

**N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)**

INDEX - 0,075 ≤ x ≤ 0,085 Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC 939-700-4

CAS -

REACH Reg. 01-2119982395-25

Note L: the classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants max: 38,56 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Most important symptoms and effects: headache, dizziness, drowsiness, nausea and other central nervous system effects.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatically treatment.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products: carbon oxides.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

**6.2. Environmental precautions**

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):2B

7.3. Specific end use(s)

Universal cutting fluid.

SECTION 8. Exposure controls/personal protection**8.1. Control parameters****Regulatory references:**

AUS Österreich
BEL Belgique
BGR България

Gesamte Rechtsvorschrift für Grenzwertverordnung 2021, Fassung vom 14.05.2023
Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail
НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ,
СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)

CHE Suisse / Schweiz

Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA)

DEU Deutschland

Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58

DNK Danmark

Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019

ESP España

Límites de exposición profesional para agentes químicos en España 2023

FRA France

Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021

FIN Suomi

HTP-VÄRDEN 2020. Koncentrationer som befunns skadliga. SOCIAL - OCH

GRC Ελλάδα

HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25

Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ «σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία»»

HUN Magyarország

Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelethez a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről

HRV Hrvatska

Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)

IRL Éire

2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)

LVA Latvija

Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)

NOR Norge

Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255

NLD Nederland


Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit


POL Polska

Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy

ROU România

Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru

		CENTRO DISTRIBUZIONE UTENSILI S.p.a.				Revision nr. 8 Dated 08/05/2024	EN
		CUT OIL F500				Printed on 09/05/2024 Page n. 5/15 Replaced revision:7 (Dated: 06/09/2022)	
SVN	Slovenija	modificarea și completarea hotărârii guvernului nr. 1.093/2006 Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19) EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2023					
GBR	United Kingdom TLV-ACGIH						
BUTANE							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
MAK	AUS	1900	800	3800	1600	STEL:60(Mow),Häufigkeit/Sch:3x	
TRK	AUS	1600	800	3800	1600		
VLEP	BEL			2370	980		
TLV	BGR	1900					
MAK	CHE	1900	800	7600	3200		
VME/VLE	CHE	1900	800	7600	3200		
AGW	DEU	2400	1000	9600	4000		
MAK	DEU	2400	1000	9600	4000		
TLV	DNK	1200	500				
VLA	ESP		1000			Gases	
VLEP	FRA	1900	800				
HTP	FIN	1900	800	2400	1000		
TLV	GRC	2350	1000				
AK	HUN	2350		9400			
GVI/KGVI	HRV	1450	600	1810	750		
OELV	IRL				1000	All Isomers	
RV	LVA	300					
TLV	NOR	600	250				
TGG	NLD	1430					
NDS/NDSch	POL	1900		3000			
MV	SVN	2400	1000	9600	4000		
WEL	GBR	1450	600	1810	750		
WEL	GBR		4			RESP	
TLV-ACGIH					1000		
PROPANE							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
MAK	AUS	1800	1000	3600	2000	STEL:60(Mow),Häufigkeit/Sch:3x	
TRK	AUS	1800	1000	3600	2000		
VLEP	BEL		1000				
TLV	BGR	1800					
MAK	CHE	1800	1000	7200	4000		
VME/VLE	CHE	1800	1000	7200	4000		

	CENTRO DISTRIBUZIONE UTENSILI S.p.a.					Revision nr. 8 Dated 08/05/2024				EN
	CUT OIL F500					Printed on 09/05/2024 Page n. 6/15 Replaced revision:7 (Dated: 06/09/2022)				
AGW	DEU	1800	1000	7200	4000					
MAK	DEU	1800	1000	7200	4000					
TLV	DNK	1800	1000							
VLA	ESP		1000							
HTP	FIN	1500	800	2000	1100					
TLV	GRC	1800	1000							
RV	LVA	1800	100							
TLV	NOR	900	500							
NDS/NDSch	POL	1800								
TLV	ROU	1400	778	1800	1000					
MV	SVN	1800	1000	7200	4000					
HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
TLV-ACGIH		1200		197		Vapore				
Health - Derived no-effect level - DNEL / DMEL										
	Effects on consumers				Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic		
Oral				125 mg/kg bw/d						
Inhalation				185 mg/m3				871 mg/m3		
Skin				125 mg/kg bw/d				208 mg/kg bw/d		
ISOBUTANE										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
VLEP	BEL			2370	980					
MAK	CHE	1900	800							
VME/VLE	CHE	1900	800							
AGW	DEU	2400	1000	9600	4000					
MAK	DEU	2400	1000	9600	4000					
HTP	FIN	1900	800	2400	1000					
OELV	IRL				1000					
TLV-ACGIH					1000					
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
TLV-ACGIH		5		10		INHAL				
Health - Derived no-effect level - DNEL / DMEL										
	Effects on consumers				Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic		



CUT OIL F500

Revision nr. 8
Dated 08/05/2024
Printed on 09/05/2024
Page n. 7/15
Replaced revision:7 (Dated: 06/09/2022)

	systemic	systemic	systemic
Inhalation	1,2 mg/m3		5,4 mg/m3

N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,000976	mg/l
Normal value in marine water	0,000098	mg/l
Normal value for fresh water sediment	0,0121	mg/kg
Normal value for marine water sediment	0,00121	mg/kg
Normal value for water, intermittent release	0,00976	mg/l
Normal value of STP microorganisms	0,69	mg/l
Normal value for the terrestrial compartment	0,00184	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers

Effects on workers

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,2 mg/kg				
Inhalation				0,3 mg/m3			VND	1,3 mg/m3
Skin				0,2 mg/kg				0,4 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with work gloves (see standard EN 374).

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	aerosol	
Colour	ochre	
Odour	waxy, of medium intensity	
Melting point / freezing point	not available	
Initial boiling point	not available	



CUT OIL F500

Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not applicable	Reason for missing data: does not apply to aerosols and gases
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not applicable	Reason for missing data: does not apply to aerosols and gases
Kinematic viscosity	not available	
Solubility	in water: insoluble; in acetone: soluble	Remark: refers to the liquid base of the spray
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,87 - 0,88 kg/dm ³	Remark: the density data refers to the liquid base without considering the propellant.
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes
Information not available.

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	50,78 %
Propellant flammability	extremely flammable
Limit of propellant flammability	1,8-9,5%

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC
Flammable liquid and vapor. Vapors can form explosive mixtures with air.

10.4. Conditions to avoid

Avoid overheating.

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

Avoid exposure to: excessive heat (prolonged period), flames, ignition sources.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

Avoid exposure to: heat sources, naked flames, direct sunlight, ignition sources.

N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)

Avoid exposure to: Sparks, naked flames, electrostatic discharges.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.



HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

Incompatible with: strong oxidising agents.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

Incompatible with: strong acids, strong bases, oxidising agents.

N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)

Incompatible with: strong oxidising agents, strong acids, strong bases.

10.6. Hazardous decomposition products

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

When heated to decomposition releases: carbon oxides, toxic gases or vapors, harsh fumes.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

Information on likely routes of exposure

Information not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

Interactive effects

Information not available.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

not classified (no significant component)

ATE (Oral) of the mixture:

not classified (no significant component)

ATE (Dermal) of the mixture:

not classified (no significant component)

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

LD50 (Dermal): > 5000 mg/kg Rabbit (OECD 402)

LD50 (Oral): > 5000 mg/kg Rat (OECD 401)

LC50 (Inhalation vapours): > 5 mg/l/4h Rat (OECD 403)

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

LD50 (Dermal): > 5000 mg/kg Rabbit (OECD 402)

LD50 (Oral): > 5000 mg/kg Rat (OECD 401)

LC50 (Inhalation vapours): > 5000 mg/m³/4h Rat (OECD 403)

N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)

LD50 (Dermal): > 2000 mg/kg Rat

LD50 (Oral): > 3313 mg/kg Rat (OECD 401)

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class.



CUT OIL F500

CARCINOGENICITY

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Toxic for aspiration.

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC**

LL0 - Pesci	100 mg/l/96h Pimephales promelas
EL0 - Crostacei	> 1000 g/kg/48h Daphnia Magna
EL0 - Alghe / Piante Acquatiche	100 mg/l/72h Pseudokirchneriella subcapitata
NOELR Alghe / Piante Acquatiche	100 mg/l/72h Pseudokirchneriella subcapitata
NOELR - Crostacei	> 10 mg/l/21d Daphnia Magna

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

LC50 - for Fish	> 1000 mg/l/96h Onchorhynchus mykiss
EC50 - for Crustacea	1000 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Algae / Aquatic Plants	> 100 mg/l 72h - Pseudokirchneriella subcapitata

N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)

LC50 - for Fish	1,3 mg/l/96h Brachydanio rerio (OECD 203)
EC50 - for Crustacea	2,05 mg/l/48h Daphnia magna (OECD 202)
EC50 - for Algae / Aquatic Plants	0,976 mg/l/72h Desmodesmus subspicatus (OECD 201)

12.2. Persistence and degradability**BUTANE**

Rapidly degradable

PROPANE

Rapidly degradable



CUT OIL F500

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

Solubility in water	Insoluble
Rapidly degradable	80% - 28d in acqua

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

Solubility in water	Negligible
Entirely degradable	31,13 - 28d (OECD 301F)

N,N-BIS(2-ETHYLHEXYL)-5-METHYL-1H-BENZOTRIAZOLE-1-METHYLAMINE (MIXTURE)

Solubility in water	Insoluble
NOT rapidly degradable	

12.3. Bioaccumulative potential

HYDROCARBONS, C9 - C11, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATIC

Partition coefficient: n-octanol/water	> 4 Log Kow
--	-------------

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

Partition coefficient: n-octanol/water	> 3,5
--	-------

Potentially bioaccumulable. However, the metabolism or physical properties can reduce bioconcentration or limit bioavailability.

12.4. Mobility in soil

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

This material has low solubility and it is assumed that floats and migrates from water to the ground. It is assumed that it is divided into the sediment and in solids suspended in the waste water. Low migration potential through soil.

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA:	UN 1950
------------------------	---------

14.2. UN proper shipping name



CUT OIL F500

ADR / RID: AEROSOLS, FLAMMABLE
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: -- Special provision: 190, 327, 344, 625	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 150 Kg Maximum quantity: 75 Kg A145, A167, A802	Packaging instructions: 203 Packaging instructions: 203

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable.

Substances in Candidate List (Art. 59 REACH)



On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None.

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the mixture.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas (Liq.)	Liquefied gas
Asp. Tox. 1	Aspiration hazard, category 1
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1B	Skin sensitization, category 1B
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:



- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

Classification and procedure used to derive it in accordance with Regulation (EC) 1272/2008 (CLP) in relation to mixtures:

Classification according to Regulation (EC) No. 1272/2008	Classification procedure
Aerosol, 1 H222+H229	Calculation method and on the basis of experimental data
Asp. Tox. 1 H304	Calculation method

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
 23. Delegated Regulation (UE) 2023/707
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)



CENTRO DISTRIBUZIONE UTENSILI S.p.a.

CUT OIL F500

Revision nr. 8
Dated 08/05/2024
Printed on 09/05/2024
Page n. 15/15
Replaced revision:7 (Dated: 06/09/2022)

EN

- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.