

TECHNICAL DATA SHEET

L630 HQ-Sil

Silicone lubricant

Multipurpose product, it forms an oily film with **anti-adhesive** properties; it protects parts from weather, if placed under cover even for long periods; **release agent**; **lubricant**, used as a sliding and release agent in the rubber, plastic and wood industry; it shows high **hydro-repellent** power and protects in moist environments; **and antistatic**. **It protects and polishes** plastics and rubber, preventing cracks.
Available as spray and liquid.

APPLICATION AREAS: different types of industrial use applications, for all metal semi-finished or finished parts, spare parts and materials to be stocked, in particular:

Shoe factories - Moulds for heels, blanking plates, glue-holder to prevent adhesion and glued binding, and so on.

Textile industries, knitwear factories - Irons, work benches, presses and cutters, hemmers, buttonhole machines, reeds, knotting heads, sliding points and passages for threads, etc.

Plastic and rubber moulding - It withstands for long and avoids interruptions and imperfect moulding.

Automatisms - For slides, stepping devices and coin devices.

Furniture factories - Slides and sliding guides, straight and circular blades, it avoids adhesion of glues and resins; it polishes finished furniture.

Typographic industries - It avoids static electricity, the adhesion of inks and glues, it prevents oxidation on plate cylinders and facilitates its removal.

Spray USE: apply the product on the relevant surfaces in the most appropriate way.

Spray FEATURES

- Appearance: colourless liquid
- Odour: characteristic
- Dropping point in °C, minimum value D-566: N.A.
- Relative density: about 0.73 gr/ml
- Water solubility: insoluble
- Lipid solubility: soluble
- Heavy metals: not present

Liquid USE: apply the product on the relevant surfaces in the most appropriate way.

Liquid FEATURES

- Odour: none
- Withstands temperature from -40°C to +250°C