

TECHNICAL DATA SHEET

P270 Puliclean

Degreaser

Solvent-based product that **evaporates quickly**, designed for **cold washing** of metal products, mechanical parts that are **very dirty because of oils and greases**, it dries quickly and it does not leave residues, it does not affect varnishes, **it is easily inflammable** and it does not contain toxic components for the ozone layer.

During operation all normal **precautions are to be adopted for easily inflammable substances** (avoid over-heating, keep far from sparks and open flames, do not smoke, avoid the accumulation of vapours by means of an appropriate aeration of the premises or suction systems equipped with an explosion-proof motor).

The storage of the product in the original containers is to be carried out in an appropriate place, covered from heat sources.

Available as spray and liquid.

APPLICATION AREAS:

it is used in all mechanical engineering and nautical fields, for cleaning parts during maintenance and reassembly.

Spray USE:

apply the product on the surface to be treated, wait for a few minutes and remove residues by means of a clean cloth or an air jet.

Liquid USE:

pure by dipping, spray or brush, in semi-automatic washing machines.

FEATURES

- Appearance: limpid liquid, colourless
- Odour: characteristic
- Dropping point in °C, minimum value D-566: N.A.
- Flash point: below 0°C
- Relative density: about 0.72 gr/ml
- Water solubility: insoluble
- Lipid solubility: soluble
- Heavy metals: not present