

**CENTRO DISTRIBUZIONE UTENSILI S.p.a**Revision nr. 7
Dated 07/11/2024

EN

PERFORMA DUE DUE

Printed on 07/11/2024

Page n. 1/14

Replaced revision:6 (Dated: 07/11/2023)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: U01310
Product name: PERFORMA DUE DUE
UFI: 7MX0-X0TF-J00D-8DYV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Emulsifiable lubricant-coolant fluid for mechanical machining.
Uses advised against: Different uses than those intended.

1.3. Details of the supplier of the safety data sheet

Name: CENTRO DISTRIBUZIONE UTENSILI S.p.a.
Full address: Via delle Gerole, 19
District and Country: 20867 CAPONAGO (MB)
ITALY
tel. +39 02 95746081
fax. + 39 02 95745182

e-mail address of the competent person

responsible for the Safety Data Sheet
Supplier:

info@cdu.net
CENTRO DISTRIBUZIONE UTENSILI S.p.a.

1.4. Emergency telephone number

For urgent inquiries refer to: CENTRO DISTRIBUZIONE UTENSILI S.p.a. +39 02 95746081
(Technical support - Office hour 8.30-13.00 - 14.00-17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: WARNING

Hazard statements:

H319 Causes serious eye irritation.
H315 Causes skin irritation.



H412	Harmful to aquatic life with long lasting effects.
Precautionary statements:	
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P305+P351+P338	IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: get medical advice / attention.
P337+P313	If eye irritation persists: get medical advice / attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents / container to in accordance with local and national regulations.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.
The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	X = Conc. %	Classification (EC) 1272/2008 (CLP)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC		
INDEX 649-466-00-2	$50 \leq x < 75$	Asp. Tox. 1 H304, Classification note according to Annex VI to the CLP Regulation: L. Substance with extract content in DMSO of less than 3% by weight, determined using the IP 346 method.
EC 265-156-6		
CAS 64742-53-6		
REACH Reg. 01-2119480375-34		
SULFONIC ACIDS, PETROLEUM, SODIUM SALTS		
INDEX -	$5 \leq x < 10$	Eye Irrit. 2 H319
EC 271-781-5		
CAS 68608-26-4		
REACH Reg. 01-2119527859-22		
1-PHENOXYPROPAN-2-OL		
INDEX -	$5 \leq x < 10$	Eye Irrit. 2 H319
EC 212-222-7		
CAS 770-35-4		
REACH Reg. 01-2119486566-23		
ALCOHOLS, C16-18 AND C18-UNSATD., ETHOXYLATED		
INDEX -	$1 \leq x < 5$	Skin Irrit. 2 H315, Aquatic Chronic 2 H411
EC 500-236-9		
CAS 68920-66-1		
REACH Reg. 01-2119489407-26		
POLYOXYETHYLENE OLEIL ETHER NEUTRALIZED CARBOXYLIC ACID		
INDEX -	$1 \leq x < 5$	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC -		
CAS 57635-48-0		
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(CARBOXYMETHYL)-.OMEGA.-(2-ETHYLHEXYL)OXY)- (4-11 EO) NEUTRALIZED		
INDEX -	$1 \leq x < 5$	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 600-837-7		
CAS 107600-33-9		
BIPHENYL-2-OL		



PERFORMA DUE DUE

Printed on 07/11/2024

Page n. 3/14

Replaced revision:6 (Dated: 07/11/2023)

INDEX 604-020-00-6

 $1 \leq x < 5$ Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Acute 1 H400
M=1

EC 201-993-5

CAS 90-43-7

REACH Reg. biocide

FATTY ACIDS, TALL-OIL, POTASSIUM SALTS

INDEX -

 $1 \leq x < 3$

Skin Corr. 1B H314, Eye Dam. 1 H318

EC 263-136-1

CAS 61790-44-1

PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT

INDEX 613-344-00-7

 $x < 0,1$ Acute Tox. 3 H311, Acute Tox. 3 H331, Acute Tox. 4 H302, STOT RE 1
H372, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute
1 H400 M=100, Aquatic Chronic 2 H411, EUH070
LD50 Oral: 500 mg/kg bw, LD50 Dermal: 790 mg/kg bw, STA Inhalation
mists/powders: 0,501 mg/l

EC 223-296-5

CAS 3811-73-2

REACH Reg. 01-2119493385-28

Note L: the classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Seek medical attention immediately. Do not use any eye drops or ointments before the examination or without the advice of an ophthalmologist.

SKIN: remove contaminated clothing. Wash immediately with plenty of running water and possibly soap the areas of the body that have come contact with the product, even if only suspected. Wash contaminated clothing before re-use.

INHALATION: take the subject to the open air and keep it at rest. In case of unwell consult a doctor.

INGESTION: call a doctor immediately. Do not induce vomiting. Do not administer anything that is not expressly authorized by the doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatically treatment.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use water jets. Use water jets only to cool the surfaces of containers exposed to fire.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

[illegible]

**SULFONIC ACIDS, PETROLEUM, SODIUM SALTS**

Predicted no-effect concentration - PNEC

Normal value in fresh water	1	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	723500000	mg/kg/d
Normal value for marine water sediment	723500000	mg/kg/d
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	868700000	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers

Effects on workers

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,833 mg/kg bw/d				
Inhalation				0,33 mg/m3				0,66 mg/m3
Skin				1,667 mg/kg bw/d				3,33 mg/kg bw/d

BIPHENYL-2-OL

Predicted no-effect concentration - PNEC

Normal value in marine water	0,00009	mg/l
Normal value for marine water sediment	0,01284	mg/kg dwt
Normal value for water, intermittent release	0,027	mg/l
Normal value of STP microorganisms	0,56	mg/l
Normal value for the terrestrial compartment	2,5	mg/kg dwt

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers

Effects on workers

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,4 mg/kg bw/d				
Inhalation				1,2 mg/m3				19,25 mg/m3
Skin				0,4 mg/kg bw/d				21,84 mg/kg bw/d

ALCOHOLS, C16-18 AND C18-UNSATD., ETHOXYLATED

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,002	mg/l
Normal value in marine water	0,002	mg/l
Normal value for fresh water sediment	86,9	mg/kg/d
Normal value for marine water sediment	86,9	mg/kg/d
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	10000	mg/l
Normal value for the terrestrial compartment	1	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers

Effects on workers

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
-------------------	-------------	----------------	---------------	------------------	-------------	----------------	---------------	------------------



Oral	25 mg/kg bw/d	
Inhalation	87 mg/m3	294 mg/m3
Skin	1250 mg/kg bw/d	2080 mg/kg bw/d

1-PHENOXYPROPAN-2-OL

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,1	mg/l
Normal value in marine water	0,01	mg/l
Normal value for fresh water sediment	0,38	mg/kg/d
Normal value for marine water sediment	0,038	mg/kg/d
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,02	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers

Effects on workers

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				3,65 mg/kg bw/d				
Inhalation								25,7 mg/m3
Skin				21 mg/kg bw/d				42 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	clear liquid	
Colour	amber	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	non-flammable	
Lower explosive limit	not applicable	
Upper explosive limit	not applicable	
Flash point	> 100 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	9,20 - 9,60	Concentration: 5 % Temperature: 20 °C
Kinematic viscosity	50 mm ² /s	Temperature: 40 °C
Solubility	emulsifiable in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,94 - 0,96 kg/dm ³	Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes
Information not available.

9.2.2. Other safety characteristics
Explosive properties not applicable

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC
Avoid exposure to: heat, naked flames, direct sunlight, sources of ignition.
ALCOHOLS, C16-18 AND C18-UNSATD., ETHOXYLATED
Avoid contact with: strong acids, oxidising agents.

10.5. Incompatible materials

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC
Incompatible with: strong acids, strong bases, oxidising agents.
PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT
Incompatible with: acids, oxidising agents.

**10.6. Hazardous decomposition products**

Information not available.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

Information on likely routes of exposure

Information not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

Interactive effects

Information not available.

ACUTE TOXICITY ATE (Inhalation) of the mixture:

not classified (no significant component)

ATE (Oral) of the mixture:

not classified (no significant component)

ATE (Dermal) of the mixture:

not classified (no significant component)

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

LD50 (Dermal):

> 5000 mg/kg Rabbit (OECD 402)

LD50 (Oral):

> 5000 mg/kg Rat (OECD 401)

LC50 (Inhalation vapours):

> 5,53 mg/l/4h Rat (OECD 403)

SULFONIC ACIDS, PETROLEUM, SODIUM SALTS

LD50 (Dermal):

> 5000 mg/kg Rabbit

LC50 (Inhalation mists/powders):

> 1,9 mg/l/4h Rat

BIPHENYL-2-OL

LD50 (Dermal):

> 5000 mg/kg Rat (OECD 402)

LD50 (Oral):

2733 mg/kg Rat (OECD 401)

PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT

LD50 (Dermal):

790 mg/kg bw

LD50 (Oral):

500 mg/kg bw

LC50 (Inhalation mists/powders):

0,5 mg/l

ALCOHOLS, C16-18 AND C18-UNSATD., ETHOXYLATED

LD50 (Oral):

> 2000 mg/kg Rat (OECD 401)

1-PHENOXYPROPAN-2-OL

LD50 (Dermal):

> 2000 mg/kg Rat

LD50 (Oral):

> 2000 mg/kg Rat

LC50 (Inhalation vapours):

> 5,4 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation.

**SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class. Viscosity: >20,5 mm²/s (40°C)

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC**

LC50 - for Fish	> 100 mg/l/96h Pimephales promelas (OECD 203)
EC50 - for Crustacea	> 10000 mg/l/48h Daphnia magna (OECD 202)
Chronic NOEC for Algae / Aquatic Plants	> 100 mg/l 72h - Pseudokirchneriella subcapitata (OECD 201)

SULFONIC ACIDS, PETROLEUM, SODIUM SALTS

LC50 - for Fish	> 10000 mg/l/96h
EC50 - for Crustacea	> 1000 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h

BIPHENYL-2-OL

LC50 - for Fish	4,5 mg/l/96h Danio rerio
EC50 - for Crustacea	2,7 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	3,57 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Fish	0,036 mg/l/21d Pimephales promelas
Chronic NOEC for Crustacea	0,0075 – 0,75 mg/l/21d Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	0,468 mg/l/72h Pseudokirchneriella subcapitata



PERFORMA DUE DUE

Printed on 07/11/2024

Page n. 10/14

Replaced revision:6 (Dated: 07/11/2023)

PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT

LC50 - for Fish 0,0073 mg/l/96h (OECD 203)

EC50 - for Crustacea 0,022 mg/l/48h (OECD 202)

EC50 - for Algae / Aquatic Plants 0,46 mg/l/72h (OECD 201)

ALCOHOLS, C16-18 AND C18-UNSATD., ETHOXYLATED

LC50 - for Fish > 1000 mg/l/96h Danio rerio (OECD 203)

1-PHENOXYPROPAN-2-OL

LC50 - for Fish > 280 mg/l/96h Pimephales promelas

EC50 - for Crustacea > 370 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h Desmodesmus subspicatus

12.2. Persistence and degradability

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

Solubility in water Insoluble

NOT rapidly degradable 31% - 28d (OECD 301F)

BIPHENYL-2-OL

Rapidly degradable 70,8-75,7% - 28d (OECD 301B)

PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT

Rapidly degradable

ALCOHOLS, C16-18 AND C18-UNSATD., ETHOXYLATED

Solubility in water Insolubile

Rapidly degradable 73% - 28d (OECD TG 301 B)

1-PHENOXYPROPAN-2-OL

Rapidly degradable 72% - 28d (OECD 301F)

12.3. Bioaccumulative potential

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

Partition coefficient: n-octanol/water > 2 Log Kow

BCF < 500

BIPHENYL-2-OL

Partition coefficient: n-octanol/water 3,18 Log Kow (OECD 107)

BCF 22

ALCOHOLS, C16-18 AND C18-UNSATD., ETHOXYLATED

Partition coefficient: n-octanol/water 6,13

12.4. Mobility in soil

Information not available.

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Not applicable.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant.

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: none.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point	3
-------	---

Contained substance

Point	75
-------	----

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

	CENTRO DISTRIBUZIONE UTENSILI S.p.a	Revision nr. 7 Dated 07/11/2024	EN
	PERFORMA DUE DUE	Printed on 07/11/2024 Page n. 12/14 Replaced revision:6 (Dated: 07/11/2023)	

Not applicable.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None.

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 3: severe hazard to waters.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the mixture.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.



H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH070	Toxic by eye contact.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

Classification and procedure used to derive it pursuant to Regulation (EC) 1272/2008 (CLP) in relation to mixtures:

Classification in accordance with Regulation (EC) n.1272/2008	Classification procedure
Eye Irrit. 2 H319	Calculation method
Skin Irrit. 2 H315	Calculation method
Aquatic Chronic 3 H412	Calculation method

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

**PERFORMA DUE DUE**

Printed on 07/11/2024

Page n. 14/14

Replaced revision:6 (Dated: 07/11/2023)

11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 15 / 16.