

**CENTRO DISTRIBUZIONE UTENSILI S.p.a.****VASELINEGREASE G320**

Revision nr. 3

Dated 20/04/2023

Printed on 02/05/2023

Page n. 1/14

Replaced revision:2 (Dated: 20/08/2019)

EN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: U052350004
Product name: VASELINEGREASE G320
UFI: FNV0-90XA-H000-2JKD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Vaseline grease.
Uses advised against: Different uses than those intended.

1.3. Details of the supplier of the safety data sheet

Name: CENTRO DISTRIBUZIONE UTENSILI S.p.a
Full address: Via delle Gerole, 19
District and Country: 20867 CAPONAGO (MB)
ITALY
tel. +39 02 95746081
fax. + 39 02 95745182

e-mail address of the competent person

responsible for the Safety Data Sheet: info@cdu.net
Supplier: CENTRO DISTRIBUZIONE UTENSILI S.p.a

1.4. Emergency telephone number

For urgent inquiries refer to: CENTRO DISTRIBUZIONE UTENSILI S.p.a +39 02 95746081
(Technical support - Office hour 8.30-13.00 - 14.00-17.30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: DANGER

Hazard statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.



VASELINEGREASE G320

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P102	Keep out of reach of children.
P211	Do not spray on an open flame or other ignition source.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.
The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	X = Conc. %	Classification (EC) 1272/2008 (CLP)
PROPANE		
INDEX 601-003-00-5	$10,34 \leq x < 31,34$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
CAS 74-98-6		
REACH Reg. 01-2119486944-21		
PETROLATUM		
INDEX -	$13,9 \leq x < 23,9$	--
EC 232-373-2		
CAS 8009-03-8		
REACH Reg. 01-2119490412-42		
BUTANE		
INDEX 601-004-00-0	$10,06 \leq x < 14,06$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7		
CAS 106-97-8		
REACH Reg. 01-2119474691-32		
WHITE MINERAL OIL (PETROLEUM)		
INDEX -	$4,16 \leq x < 7,16$	--
EC 232-455-8		
CAS 8042-47-5		
REACH Reg. 01-2119487078-27		
ISOBUTANE		
INDEX 601-004-00-0	$3,79 \leq x < 6,79$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 200-857-2		
CAS 75-28-5		
REACH Reg. 01-2119485395-27		
1,3-BUTADIENE		
INDEX 601-013-00-X	$0,02 \leq x < 0,05$	Flam. Gas 1A H220, Press. Gas (Comp.) H280, Carc. 1A H350, Muta. 1B H340, Classification note according to Annex VI to the CLP Regulation: D
EC 203-450-8		
CAS 106-99-0		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants max: 52.24 %



SECTION 4. First aid measures

4.1. Description of first aid measures

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary:

INHALATION: remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person.

EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatically treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.



VASELINEGREASE G320

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany): 2B

7.3. Specific end use(s)

Vaseline grease.

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

AUS	Österreich	Gesamte Rechtsvorschrift für Grenzwerteverordnung 2021, Fassung vom 17.06.2021
BEL	Belgique	Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA)
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte, MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSÖVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
IRL	Éire	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom TLV-ACGIH	EH40/2005 Workplace exposure limits (Fourth Edition 2020) ACGIH 2022

WHITE MINERAL OIL (PETROLEUM)**Threshold Limit Value**

**CENTRO DISTRIBUZIONE UTENSILI S.p.a.**

Revision nr. 3

EN

Dated 20/04/2023

VASELINEGREASE G320

Printed on 02/05/2023

Page n. 5/14

Replaced revision:2 (Dated: 20/08/2019)

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	CHE	5				INHAL
AGW	DEU	5		20		RESP
MAK	DEU	5		20		RESP
TLV	ROU	5		10		
TLV-ACGIH		5				

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers

Effects on workers

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				25 mg/kg bw/d				
Inhalation				34,78 mg/m3				164,56 mg/m3
Skin				93,02 mg/kg bw/d				217,05 mg/kg bw/d

BUTANE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	1900	800	3800	1600	STEL:60(Mow),Häufigkeit/Sch:3x
TRK	AUS	1600	800	3800	1600	
VLEP	BEL			2370	980	
TLV	BGR	1900				
MAK	CHE	1900	800	7600	3200	
VME/VLE	CHE	1900	800	7600	3200	
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
TLV	DNK	1200	500			
VLA	ESP		1000			Gases
TLV	EST	1500	800			
VLEP	FRA	1900	800			
HTP	FIN	1900	800	2400	1000	
TLV	GRC	2350	1000			
AK	HUN	2350		9400		
GVI/KGVI	HRV	1450	600	1810	750	
OELV	IRL				1000	All Isomers
RV	LVA	300				
TLV	NOR	600	250			
TGG	NLD	1430				
NDS/NDSch	POL	1900		3000		
MV	SVN	2400	1000	9600	4000	
WEL	GBR	1450	600	1810	750	
WEL	GBR		4			RESP



VASELINEGREASE G320

TLV-ACGIH

1000

PROPANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	1800	1000	3600	2000	STEL:60(Mow),Häufigkeit/Sch:3x
TRK	AUS	1800	1000	3600	2000	
VLEP	BEL		1000			
TLV	BGR	1800				
MAK	CHE	1800	1000	7200	4000	
VME/VLE	CHE	1800	1000	7200	4000	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
TLV	DNK	1800	1000			
VLA	ESP		1000			
TLV	EST	1800	1000			
HTP	FIN	1500	800	2000	1100	
TLV	GRC	1800	1000			
RV	LVA	1800	100			
TLV	NOR	900	500			
NDS/NDSch	POL	1800				
TLV	ROU	1400	778	1800	1000	
MV	SVN	1800	1000	7200	4000	

ISOBUTANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	BEL			2370	980	
MAK	CHE	1900	800			
VME/VLE	CHE	1900	800			
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
HTP	FIN	1900	800	2400	1000	
OELV	IRL				1000	
TLV-ACGIH					1000	

PETROLATUM

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		2				RESP



Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	aerosol	
Colour	colourless	
Odour	odourless	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	Note: does not apply to aerosols
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not applicable	Not technically feasible
Kinematic viscosity	not available	
Solubility	in water: insoluble; in acetone: soluble	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not available	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes
Information not available.

9.2.2. Other safety characteristics



VOC (Directive 2010/75/EU)	83.24 %
Propellant flammability	extremely flammable
Limit of propellant flammability	1,8-9,5%

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

WHITE MINERAL OIL (PETROLEUM)

Avoid exposure to: heat, naked flames, direct sunlight, ignition sources.

PETROLATUM

Avoid exposure to: heat sources, naked flames, direct sunlight, sources of ignition.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

WHITE MINERAL OIL (PETROLEUM)

Avoid contact with: acids, strong bases, oxidising agents.

PETROLATUM

Avoid contact with: acids, strong bases, oxidising agents.

10.6. Hazardous decomposition products

WHITE MINERAL OIL (PETROLEUM)

When heated to decomposition releases: harmful and flammable gases or vapors.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

Information on likely routes of exposure

Information not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

Interactive effects

Information not available.



VASELINEGREASE G320

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

not classified (no significant component)

ATE (Oral) of the mixture:

not classified (no significant component)

ATE (Dermal) of the mixture:

not classified (no significant component)

WHITE MINERAL OIL (PETROLEUM)

LD50 (Dermal):

> 5000 mg/m3 Rabbit (OECD 402)

LD50 (Oral):

> 5000 mg/kg Rat (OECD 401)

LC50 (Inhalation vapours):

> 5000 mg/m3 Rat (OECD 403)

PETROLATUM

LD50 (Dermal):

> 2000 mg/kg Rabbit (OECD - 402)

LD50 (Oral):

> 5000 mg/kg Rat (OECD - 401)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class.

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity**WHITE MINERAL OIL (PETROLEUM)**

LC50 - for Fish

> 100 mg/l/96h

EC50 - for Crustacea

100 mg/l/48h



VASELINEGREASE G320

EC50 - for Algae / Aquatic Plants

100 mg/l/72h

PETROLATUM

LC50 - for Fish

> 100 mg/l/96h Pimephales promelas (OECD - 203)

EC50 - for Crustacea

> 10000 mg/l/48h Daphnia magna (OECD - 202)

12.2. Persistence and degradability

WHITE MINERAL OIL (PETROLEUM)

Rapidly degradable

BUTANE

Rapidly degradable

PROPANE

Rapidly degradable

PETROLATUM

Solubility in water

Insoluble

NOT rapidly degradable

31% OECD 301F

12.3. Bioaccumulative potential

WHITE MINERAL OIL (PETROLEUM)

Partition coefficient: n-octanol/water

> 3.5

12.4. Mobility in soil

Information not available.

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

**CENTRO DISTRIBUZIONE UTENSILI S.p.a.**

Revision nr. 3

EN

Dated 20/04/2023

VASELINEGREASE G320

Printed on 02/05/2023

Page n. 11/14

Replaced revision:2 (Dated: 20/08/2019)

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant.

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P3a.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40



VASELINEGREASE G320

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable.

Substances in Candidate List (Art. 59 REACH)On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.Substances subject to authorisation (Annex XIV REACH)

None.

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls

Information not available.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 3: severe hazard to waters.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the mixture.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Press. Gas (Liq.)	Liquefied gas
Press. Gas (Comp.)	Compressed gas
Carc. 1A	Carcinogenicity, category 1A
Muta. 1B	Germ cell mutagenicity, category 1B
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H350	May cause cancer.
H340	May cause genetic defects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)

**VASELINEGREASE G320**

- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

Classification and procedure used to derive it in accordance with Regulation (EC) 1272/2008 (CLP) in relation to mixtures:

Classification according to Regulation (EC) No. 1272/2008	Classification procedure
Aerosol 1 H222+H229	Based on experimental data

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:



CENTRO DISTRIBUZIONE UTENSILI S.p.a.

Revision nr. 3

EN

Dated 20/04/2023

VASELINEGREASE G320

Printed on 02/05/2023

Page n. 14/14

Replaced revision:2 (Dated: 20/08/2019)

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.